

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
29 November 2001 (29.11.2001)


PCT

(10) International Publication Number  
**WO 01/89393 A1**

- (51) International Patent Classification<sup>7</sup>: **A61B 17/10**
- (21) International Application Number: **PCT/US01/16025**
- (22) International Filing Date: **19 May 2001 (19.05.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/205,444 19 May 2000 (19.05.2000) US  
60/205,741 19 May 2000 (19.05.2000) US  
60/253,970 29 November 2000 (29.11.2000) US  
PCT/US01/07349 5 March 2001 (05.03.2001) US
- (72) Inventor; and  
(75) Inventor/Applicant (for US only): **GAMBALE, Richard, A.** [US/US]; 382 Dunstable Road, Tynsgboro, MA 01879 (US).
- (74) Agent: **LORUSSO, Mark, D.**; Kirkpatrick & Lockhart LLP, 75 State Street, Boston, MA 02109 (US).
- (81) Designated States (national): **JP, US.**
- (84) Designated States (regional): **European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).**
- Published:  
— with international search report  
— with amended claims
- (71) Applicant (for all designated States except US): **C.R. BARD, INC.** [US/US]; 730 Central Avenue, Murray Hill, NJ 07974 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **TISSUE CAPTURING AND SUTURING DEVICE AND METHOD**



(57) Abstract: A combination tissue apposition and suture capturing device (100) for performing endoscopic procedures typically in the gastro-esophageal tract. The device (100) is particularly adapted for forming multiple plications used in a gastroplasty procedure devised to cure or ameliorate gastro-esophageal reflux disease. The device includes a tissue sewing capsule (102) attached to the distal end of an endoscope having a needle (120) that is deposited in a capsule (102) distal tip cavity following the suturing of a tissue fold and retrieved to enable the suturing of a subsequent tissue fold without the need for multiple intubations. A suture clip delivery device (200) is also disclosed that is adapted to fit within the capsule (102) to enable suture (118) capture without the need for multiple intubations. The combination device eliminates the need for an overtube and maximizes the speed efficiency of the gastroplasty procedure. A method for using the combination device is also disclosed.

WO 01/89393 A1

## TISSUE CAPTURING AND SUTURING DEVICE AND METHOD

### Cross-Reference to Related Applications

A claim of benefit is made to U.S. Provisional Applications Nos. 60/205,741 filed 19 May 2000, 60/205,444 filed 19 May 2000, 60/253,970 filed 29 November 2000 and PCT Application No. PCT/US01/07349, the contents of which are incorporated in their entirety herein by reference.

### Field of the Invention

The present invention relates to a novel combination of endoscopic tissue apposition devices and suture clip delivery devices. Specifically, the invention provides an endoscopic apposition device configured to collect and secure a plurality of tissue portions with a single intubation of the device. The invention is applicable to both flexible and rigid endoscopy.

### Background of the Invention

Endoscopic apposition devices are devices that can be used in the body of a patient without the need to make an external incision in the patient, the device being controlled externally of the patient by endoscopic means. Apposition devices may comprise a sewing or stapling device for use in flexible endoscopy, though it is also applicable to devices for use in rigid endoscopy.

Endoscopic tissue apposition devices are useful to help perform a gastroplasty procedure to correct a condition known as gastro-esophageal reflux disease (GERD). This condition, believed to afflict as many as 15,000,000 individuals in the United States alone, results from the inability of the sphincter muscle (known as the lower esophageal or cardiac sphincter), at the junction between the stomach and the esophagus to function properly. Such malfunction enables reflux of stomach acid into the esophagus. The object of the gastroplasty procedure is to stitch together portions

of stomach tissue into plications in a region proximal to the malfunctioning sphincter to reduce the cross-sectional area of the gastro-esophageal juncture and mimic the valve-like function of the sphincter.

To perform the procedure, an apposition device, such as a sewing capsule is attached to the end of a viewing endoscope and is inserted through a patient's esophagus to form a plurality of stitches in stomach tissue slightly below the sphincter. The sewing capsule has an aspiration port for generating negative pressure to suction stomach wall tissue into the sewing capsule. A first stitch is made through the stomach tissue to one side of the esophagus, and a second stitch is made, with the same suture thread, in stomach tissue adjacent to the first stitch. The two stitches then are drawn together to pull together the diametrically opposed, stitched stomach portions. In a preferred procedure, a tubular configuration having a somewhat figure-eight cross-sectional configuration is formed.

In accordance with what has been, until now, the conventional procedure followed, after the sutures are applied, the endoscope is removed from the patient and a knot is tied with the free ends of the suture thread that extend outside of the patient to maintain the figure-eight configuration. The knot is pushed down to the site of the sutures by a thread guide device that has been positioned at the distal end of the endoscope. To help navigate the knot to a location where it will effectively hold the tissue, the knot is viewed through the viewing channel of the endoscope as it is guided to the stomach. To be visible through the endoscope, the knot must be maintained in front of the viewing channel port at the distal face of the endoscope while positioning the thread guide device so as not to block the viewing channel.

The suturing and knotting procedure is repeated several times at longitudinally spaced intervals to create a plurality of figure-eight configurations extending longitudinally of the esophagus into the stomach. Suturing the stomach tissue in this manner essentially lengthens the esophageal passage and defines a structure having a valving action that is proven effective to prevent gastro-esophageal reflux. After a sufficient number of knots and sutures have been placed, a thread cutter, also operable through the endoscope, may be employed to cut the suture thread at points that are close to the tissue.

Endoscopic sewing devices are described in, for example, U.S. Pat. Nos. 5,080,663 and 5,792,153. Those patents disclose a sewing device for passing a

thread through a tissue portion, which comprises a hollow needle movable between a first position in which it is out of the said tissue portion and a second position in which it passes through the said tissue portion, and a thread carrier adapted to be attached to the thread and being receivable within the hollow needle. The sewing device comprises a body, which defines a cavity within which the tissue portion can be held by means of suction, and the hollow needle is mounted for movement in the body between the first and second positions.

U.S. patent no. 5,792,153 discloses two suturing device embodiments: a single stitch sewing device and a multiple stitch sewing device. In the single stitch device, a thread carrier is transported by the needle through the tissue as the latter passes from its first position to its second position. When the needle returns to its first position, the thread carrier is left behind in the distal end of the sewing capsule. In the multiple stitch device, the same procedure occurs, but it is followed by a further step in which the hollow needle travels from its first position to its second position, picks up the thread carrier, and returns it. A second stitch may be formed during the next step. The whole sequence of steps is repeated as many times as may be required to form the desired number of stitches.

Similar advancements have been made with respect to the suture securing step that follows the stitching step. One such improvement is disclosed in U.S. Patent No. 5,584,861 to Swain. The Swain patent discloses a suture clip and suture clip delivery device that is used in place of half hitch knots. The disclosed suture clip is a cylinder with a plug that can be releasably secured in the cylinder. The disclosed suture clip delivery device includes a tube, the distal end of which has a recess for receiving the suture clip. An axially movable stirrup is provided at the distal end that has the capacity to be moved from a first position that secures the suture clip to the tube and a second position that allows for the suture clip to be removed from the recess.

An aperture is provided in the cylinder to receive the suture. The cylinder is advanced over the suture that exits from a proximal end of the cylinder and enters the tube. An aperture in a sidewall of the tube provides egress for the suture. The plug is then advanced down the tube and into the cylinder. The interfacing walls of the cylinder and plug capture the suture. A pusher is used to force the plug into the cylinder while the stirrup maintains the suture clip in the recess. Following plug

insertion, the stirrup, which is offset from the center axis of the tube, is advanced distally from the distal end of the tube to release the suture clip from the tube.

With all the improvements provided by the sewing capsules and suture securing devices, significant problems persist with the described gastroplasty procedure. One of the significant problems is the time and number of intubations needed to perform the various procedural steps endoscopically. Due to a number of concerns, a patient is typically anesthetized for no more than approximately 40 minutes. In this period of time, procedures such as the gastroplasty procedure must be performed to completion.

Minimizing the number of intubations and reducing the procedure time during which the patient must be kept under conscious sedation are significant considerations in any endoscopic procedure. In the gastroplasty procedure, several intubations have to be performed to create several plications. The prior art suturing devices must be withdrawn from the patient for each successive stitch made with single-stitch embodiments and must otherwise be repositioned for each stitch made with multi-stitch embodiments. The same is true of the suture securing devices. The devices must be withdrawn and repositioned between successive suture securing steps. The use of such devices is invariably long and cumbersome. There is a need to provide an endoscopic tissue apposition device and suture securing device that minimizes procedure time and the number of intubations while still joining the same number of tissue plications together during the procedure.

To reduce the trauma experienced by a patient having multiple devices intubated numerous times for one gastroplasty procedure, an overtube is placed in the gastro-esophageal tract. Although an overtube provides a barrier between the devices used to perform the procedure and the luminal walls of the tract, the act of inserting the relatively large diameter tube into the tract and the presence of the tube in the tract are perhaps the most significant sources of patient discomfort. There is a need to eliminate the requirement for an overtube to perform the described gastroplasty procedure. The invention disclosed herein provides such an improvement.

It is among the general objects of the invention to provide a tissue apposition device and suture securing device that, in combination, eliminate the need to use an overtube when performing a gastroplasty procedure. A further object is to provide a

tissue apposition device that is adapted to receive a secure securing device to eliminate the need for multiple intubations to secure a plurality of tissue plications required to attach or repair internal tissue by a tissue securement mechanism comprising suture or staples. It is another object of the invention to provide an endoscopic apposition device that is simple and economical to fabricate by injection molding techniques. It is another object of the invention to provide a tissue apposition device having longitudinal flexibility to be easily navigable through a natural body lumen while mounted at the distal end of an endoscope. It is another object of the invention to provide a simplified tissue suture means having an anchor at one end which can remain on the through side of tissue during the process of tissue securement. These and other objects of the invention will become apparent from a reading of the following sections.

It is to be appreciated that the combination tissue apposition and suture securing device disclosed herein has a potentially wide range of applications including, but not limited to, the attachment of devices, e.g., a pH monitor to the gastrointestinal wall, the closure of perforations or ulcers, the creation of anastomoses, plication formation to address severe obesity and polyp plications. The device can be used with an endoscope, can be formed as the terminus of a catheter in combination with a visualization device such as an fiberoptic eye wire as is known in the art.

#### **Summary of the Invention**

The present invention pertains to improvements to endoscopic apposition device and suture clip delivery devices. The improvements may be embodied in a tissue apposition device similar to those disclosed in U.S. patent nos. 5,792,153 or 5,080,663, or a stapling device such as is disclosed in U.S. patent no. 5,037,021. The disclosures of the above listed patents are incorporated by reference herein, in their entirety. The prior art endoscopic tissue apposition devices provided a mechanism for capturing only a single fold with one intubation. The present invention provides a tissue apposition device capable of capturing multiple tissue folds and securing the sutures used to capture the folds with one intubation. The elimination of the need for multiple intubations eliminates the need for an overtube with respect to endoscopic procedures performed in the gastro-esophageal tract.

The device is comprised of a generally cylindrically shaped capsule attachable to the distal end of an endoscope, preferably a flexible viewing endoscope. The capsule comprises, in one embodiment, a body having an arc shaped suction port into which can be captured portions of tissue. The suction port defines an opening to a vacuum chamber. The vacuum chamber is operated through a vacuum source line that can extend interiorly or exteriorly to the endoscope.

Application of vacuum pressure causes tissue to be suctioned into the suction port and into the vacuum where a needle assembly comprising a needle releasably locked to a pusher via mating surfaces and an outer locking sleeve is adapted to carry a suture in a distal axial direction through into and through the tissue and into a distal tip of the capsule. Formed in the distal tip of the capsule is a cavity adapted to receive the needle assembly. A pair of springs are oriented parallel in the cavity for receiving the needle assembly. Distal faces of the springs engage a proximal edge of the needle and provide a restraining force to retraction of the needle. The locking sleeve is proximally retracted which allows the pusher to disengage from the needle that remains restrained by the springs. The pusher is retracted to allow for the release of the sutured tissue fold.

Following release of the tissue fold, the pusher is re-advanced into the distal tip of the capsule. The locking sleeve is also advanced to lock the needle onto the pusher. Proximal retraction of the pusher in a locked condition with the needle overcomes the restraining force of the springs that flex radially outwardly to allow the needle to be retracted into the proximal end of the capsule. The needle assembly is now in a condition to implant a suture in a second tissue fold. The process can be continually repeated for virtually any selected number of tissue folds, all of which will be connected by a single suture, all with a single intubation.

The tissue apposition device of the present invention offers another advantage over previous designs in that the entire capsule body may be injection molded from a polymer material. A single piece injection molded unit is easier to produce than previous capsule designs, which were machined from metal and comprise several assembled components.

In another aspect of the invention, the tissue apposition capsule body is adapted to utilize and receive a novel tissue suturing device. One tissue securement mechanism embodiment comprises sutures having anchoring elements at one end

that permit them to be passed through tissue and then become anchored behind the tissue layer to permit suturing and retention of the fold of tissue. The anchoring element of the special suture material, such as polypropylene, may comprise a cylindrical tube with detents formed in a sidewall of the tube. A needle having a longitudinal slot and a channel is adapted to receive the anchor or tag and deposit it in the distal tip of the capsule. In this embodiment, the needle is retrieved with the pusher and the tag is retained in the capsule distal tip by virtue of the interaction of the detents with the springs. To allow release of the tag from the needle, the locking sleeve is only partially retracted to allow the distal end of the needle to expand radially outwardly while the proximal end is radially restrained to maintain engagement with the pusher. Following release of the sutured tissue fold, the needle/pusher assembly is reintroduced into the distal tip and the locking sleeve fully advanced to retrieve the tag. In an alternate embodiment, the tag is released with the sutured tissue fold and the needle is retracted out of the endoscope for the loading of another anchor for insertion into another tissue fold.

Also described herein is a suture clip delivery device adapted for navigation through the working channel of an endoscope and through the capsule channel adapted to receive the needle assembly. The delivery device comprises a multi-coaxial catheter with a three or four finger collet jaw affixed at a distal end. The catheter has a distal end from which the collect fingers distally project. The collet fingers are made of a material such as stainless steel or an engineering grade of plastic that allow the collet fingers to flex or spring from a pre-biased first open position to a second closed position and back to the first position. Alternatively, the collet fingers can be designed to flex or spring from a pre-biased first closed position to a second open position and back to the first position. The collet fingers define a cage within which a suture clip assembly is premounted. The cage is defined proximally by a distal end of the collet body and distally by flanges extending radially inwardly from the distal ends of the collet fingers. In one embodiment, the case is sized so that a plurality of suture clip plugs can be preloaded into the cage along with a single suture clip ring. By biasing the collet fingers in an open position, the need for cam surfaces and cam followers is eliminated.

In one embodiment, a separate control surface provided coaxially about the collet cage is employed to slide the outer sliding sleeve relative to the collet cage and



the pusher. With any of the embodiments, the outer sliding sleeve is provided to secure the collet fingers in a closed position when placed in a distally advanced position. The outer sliding sleeve performs the additional function of severing the suture at a point proximal to the suture clip after engagement of the suture upon proximal retraction. One or more suture slots are provided in the distal end of the outer sliding sleeve to provide suture exits. A distal end of the suture slots can be sharpened to sever the suture. Upon proximal retraction of the outer sliding sleeve, the distal end of suture slot engages the suture and severs it when the distal end of the suture slot travels proximally to a cutting edge formed at or near the proximal end of the collet fingers. The design of the delivery device enables the suture clip to be cinched in close proximity to the sutured tissue as well as allow for the severing of the suture tails and release of the suture from the delivery device in one step.

The suture clips adapted for use with the suture clip delivery device are comprised of a plug and a ring that are configured to allow a suture to inter-wind through the clip in such a manner that the clips move with minimal friction while in an open position. The plug is a headless design that reduces abrasion of the suture as it exists the suture clip ends. In a closed position, the clip captures the suture by frictional engagement. The ring and plug components of the clip can be provided with interlocking features for enhancing the suture capturing effect.

Once threaded into the ring and plug, the suture is passed through finger slots formed between adjacent collet fingers and out the suture slot of the outer sliding sleeve. This enables the suture tails to be channeled externally of the catheter for removal at the proximal end of the catheter outside the patient after the tails have been severed at a point proximal to the now assembled suture clip. The catheter operator may thread a suture through a clip and then load the clip into the tooling or thread the suture through a premounted clip. After positioning the delivery system at the sutured tissue site, the device operator activates the handle to apply a distally directed force to the clip, thereby locking it to the suture. The application of force secures the clip components thus capturing the suture material within the mating surfaces. A second, proximally directed force is applied to the sliding sleeve to release radial restraint on the collet fingers that allows the secured suture clip to be deployed and to sever the suture tails in close proximity to the suture clip.

**Brief Description of the Drawings**

The foregoing and other objects and advantages of the invention will be appreciated more fully from the following further description thereof, with reference to the accompanying drawings wherein:

FIG. 1 is a perspective view of a suture capsule with a locking handle removed according to one embodiment of the invention.

FIG. 2 is a perspective view of a needle assembly adapted for use in a suture capsule according to one embodiment of the invention.

FIG. 3 is a partial sectional view of a capsule/locking sleeve/needle assembly according to one embodiment of the invention.

FIG. 4 is a partial sectional view of a capsule/needle assembly according to one embodiment of the invention.

FIG. 5 is a partial sectional view of a capsule/locking sleeve/needle assembly according to another embodiment of the invention.

FIG. 6 is a partial sectional view of a needle assembly with a suture secured to the needle disengaged from a pusher in a distal end of a suture capsule according to one embodiment of the invention.

FIG. 7 is a partial sectional view of a suture capsule vacuum chamber and distal cavity with a needle assembly lodged in the distal cavity according to one embodiment of the invention.

FIG. 8 is a partial sectional view of a needle assembly with a retracted locking sleeve according to one embodiment of the invention.

FIG. 9 is a top perspective view of the distal end of a needle assembly with a retracted locking sleeve according to one embodiment of the invention.

FIG. 10A is a partial side elevational view of a suture capsule/endoscope assembly with tissue suctioned into the suction port/vacuum chamber according to one embodiment of the invention.

FIG. 10B is a partial side elevational view of a suture capsule/endoscope assembly with tissue suctioned into the suction port/vacuum chamber with a suture/tag assembly piercing the tissue according to one embodiment of the invention.

FIG. 10C is a partial side elevational view of a suture capsule/endoscope assembly with a released first tissue mound with embedded suture and distal anchor tag and a

second tissue mound suctioned into the suction port/vacuum chamber with a suture/tag assembly piercing the second tissue mound according to one embodiment of the invention.

FIG. 10D is a partial side elevational view of a suture capsule/endoscope assembly with released first and second tissue mounds with a single suture embedded in each tissue mound with separate distal anchor tags.

FIG. 11 is a side elevational view of a tissue plication with a suture piercing the plication mound halves and secured with a suture clip.

FIG. 12 is a schematic view of a suture capsule/endoscope assembly according to one embodiment of the invention.

FIG. 13 is a tissue plication secured with a suture clip according to one embodiment of the invention.

FIG. 14 is a tissue plication secured with a suture clip according to another embodiment of the invention.

FIG. 15A is a top view of a needle/pusher assembly according to one embodiment of the invention.

FIG. 15B is a side elevational view of the needle/pusher assembly shown in FIG. 15A.

FIG. 16 is a sectional view of the needle/pusher assembly shown in FIGS. 15A and 15B.

FIG. 17 is a perspective view of a needle assembly according to one embodiment of the invention.

FIG. 18A is a side elevational view of a suture capsule/endoscope assembly with tissue suctioned into the suction port and vacuum chamber according to one embodiment of the invention.

FIG. 18B is a side elevational view of a suture capsule/endoscope assembly with tissue suctioned into a suction port and vacuum chamber and with a needle assembly advanced to a proximal end of the tissue according to one embodiment of the invention.

FIG. 18C is a side elevational view of a suture capsule/endoscope assembly with a needle/suture/tag assembly advanced distally through the tissue according to one embodiment of the invention.

FIG. 18D is a side elevational view of a suture capsule/endoscope assembly with a partially retracted needle and a suture tag assembly releasably locked into a distal end of the suture capsule according to one embodiment of the invention.

FIG. 18E is a side elevational view of a suture capsule/endoscope assembly with a fully retracted needle and a released tissue mound pierced by a suture.

FIG. 18F is a side elevational view of a suture capsule/endoscope assembly with a released tissue mound pierced by a suture and a distally advanced needle encompassing a suture anchoring tag according to one embodiment of the invention.

FIG. 18G is a side elevational view of a suture capsule/endoscope assembly with a released tissue mound and a retracted needle/tag assembly according to one embodiment of the invention.

FIG. 18H is a side elevational view of a suture capsule/endoscope assembly with a released tissue mound pierced by a suture and a second tissue mound suctioned into a suction port and vacuum chamber with a needle/tag assembly partially piercing the second mound according to one embodiment of the invention.

FIG. 18I is a side elevational view of a suture capsule/endoscope assembly with two released tissue mounds pierced by a suture with a needle/tag assembly in a retracted position according to one embodiment of the invention.

FIG. 18J is a side elevational view of a suture capsule/endoscope assembly with two released tissue mounds pierced by a suture with a suture clip delivery device partially advanced in the suture capsule according to one embodiment of the invention.

FIG. 18K is a side elevational view of a suture capsule/endoscope assembly with two released tissue mounds pierced by a suture with a suture clip delivery device fully advanced in the suture capsule in a pre-cinched state according to one embodiment of the invention.

FIG. 18L is a side elevational view of a suture capsule/endoscope assembly with two released tissue mounds pierced by a suture and cinched with a suture clip secured to the suture and being deployed by a suture clip delivery device according to one embodiment of the invention.

FIG. 18M is a side elevational view of a suture capsule/endoscope assembly with a cinched plication and a partially retracted suture clip delivery device according to one embodiment of the invention.

FIG. 18N is a side elevational view of a suture capsule/endoscope assembly with a tag retention detent in the capsule distal end according to one embodiment of the invention.

FIG. 18O is a side elevational view of a suture capsule/endoscope assembly without a tag retention detent in the capsule distal end according to one embodiment of the invention.

FIG. 19 is a somewhat diagrammatic view of a suture capsule according to one embodiment of the invention.

FIG. 20 is a partial sectional somewhat diagrammatic view of a suture capsule suction port and distal end according to one embodiment of the invention.

FIG. 21 is a side perspective view of a suture clip delivery device distal collet cage with a suture threaded through the collet cage according to one embodiment of the invention.

FIG. 22 is a top plan view of a suture capsule with a suture clip delivery device advanced through the capsule.

FIG. 23 is a side partial sectional view of a suture clip delivery device collet cage with a disassembled suture clip plug and ring and a suture threaded through the delivery device according to one embodiment of the invention.

FIG. 24 is a side partial sectional view of a suture clip delivery device with a cinched suture clip according to one embodiment of the invention.

FIG. 25 is a side partial sectional view of a suture clip delivery device with a cinched suture clip and a severed suture according to one embodiment of the invention.

FIG. 26 is a side view of a suture clip delivery device including collet cage and handle assembly with a suture threaded through the collet cage and a sliding cutter handle in a distal position according to one embodiment of the invention.

FIG. 27 is a side view of a suture clip delivery device including collet cage and handle assembly with a suture threaded through the collet cage and severed and with a sliding clutter handle in a retracted position.

FIGS. 28A – 30 show successive steps in the operation of a prior art single stitch sewing device.

### **Detailed Description of the Preferred Embodiment**

A description of the embodiments of the present invention is best presented in conjunction with an explanation of the operation of a prior art tissue apposition device, which this invention serves to improve. FIGS. 28A-30 depict a prior art endoscopic suturing device disclosed in U.S. patent no. 5,792,153. FIG. 28A shows the distal end of a flexible endoscope **90**, on which a sewing device **2** is attached. The endoscope is provided with a viewing channel, which is not shown, but which terminates at a lens on the distal face of the endoscope. The endoscope is further provided with a biopsy or working channel **3**, and a suction channel **4** the proximal end of which is connected to a source of vacuum (not shown). The suction channel **4** may comprise a separate tube that runs along the exterior of the endoscope, rather than an internal lumen as shown. The sewing device **2** has a tube **5**, which communicates with the suction pipe **4** and has a plurality of perforations **6** therein. These perforations communicate with an upwardly open vacuum chamber **7** formed in the sewing device.

A hollow needle **8** is mounted in the biopsy channel **3**, with its beveled tip extending into the sewing device. The needle has a channel **9** extending therethrough. A flexible, wire-wound cable **10** has its forward end attached to the rear of the needle **8**, and a center wire **11** runs within the cable **10**, along the entire length thereof, and is longitudinally movable with respect thereto. The diameter of the wire **11** is such that it is longitudinally movable within the channel **9** and, in the position shown in FIG. 28A, the forward end portion of the wire **11** extends into the rear end portion of the channel **9**. A thread carrier in the form of a tag **12** is slidably and releasably mounted in the channel **9**. The tag is shown in detail in FIG 28B. The tag is hollow and has an aperture **13** extending through the sidewall thereof. As can also be seen in FIG. 1, one end of a thread **14** is secured to the tag by passing it through the aperture **13** and tying in the end of a knot **15** of sufficient size to prevent the thread escaping from the tag. The tag may be made from a relatively rigid material such as stainless steel.

At the distal end of the sewing device is defined a hollow head portion **16** defining a chamber **20** therein. Between the chamber **20** and the cavity **7** is a wall **17**, in which an aperture **18** is formed. The aperture **18** has a diameter that is marginally greater than the external diameter of the needle **8**, and is aligned therewith. The clearance between the needle **8** and the aperture **18** must be sufficiently small to

prevent tissue being forced through the aperture and causing the needle to jam. Finally, FIG. 28A shows a portion of the patient's tissue 19, in which a stitch is to be formed.

In operation, suction is applied to the suction pipe 4, and thence, via the perforations 6 in the tube 5 to the cavity 7. This sucks into the cavity a U-shaped portion 19a of the tissue 19, as shown in FIG. 29. The hollow needle 8 is pushed through the U-shaped tissue portion 19a by extending distally the wire-wound cable 10 and associated needle 8. After full advancement of the needle through both folds of the U-shaped tissue portion, the tip portion of the needle 8 is distal to the wall 17 and within the chamber 20 in the hollow head portion 16. Distal movement of wire 11, slidably received within the wound cable 10, pushes the tag 12 out of the channel 9 and into the chamber 20 where it rotates out of alignment with aperture 18 to become captured in the chamber.

The wire 11 is then withdrawn proximally, followed by proximal withdrawal of the cable 10, to withdraw the needle 8 from the tissue portion 19a. The suction is then discontinued allowing the U-shaped tissue portion 19a to be released from the cavity 7. As shown in FIG. 30, the released tissue is left with a suture thread 14 passing through the two layers of tissue that form the U-shaped fold 19a. One end of the suture is joined to the tag 12 that remains captured in the chamber 20 and the other end of the suture extends through the patient's esophagus and out of the mouth. Finally, the endoscope and dewing device are withdrawn from the patient. In so doing, the thread 14 is pulled partially through the tissue portion 19a, as the captured tag 12 is withdrawn proximally and brought outside the patient.

With both ends of the thread 14 outside of the patient, the thread can be knotted and the knot endoscopically pushed down to the suture site and severed by an endoscopic knot pusher such as that disclosed in U.S. Pat. No. 6,010,515 (Swain et al). As an alternative to tying a knot, a suture lock or clip may be guided over the suture thread, down the esophagus and secured via an endoscope or suitable delivery catheter to hold the suture thread tight against the tissue. Examples of suitable suture locks and delivery systems are disclosed in PCT Application PCT/US01/ filed March 5, 2001, the contents of which are incorporated herein by reference. In using the endoscopic suturing device to treat G.E.R.D. it is believed that capture of multiple tissue portions and suturing and gathering them together provide an effective

treatment. To accomplish this using the prior art device, multiple intubations of the endoscope down the patient's esophagus are required. Once, multiple (tissue portions, have been captured and sutured with thread, they are gathered together and secured by tying of surgical knots in the thread or application of suture lock devices. Each step in the process requires separate intubations which prompts the need for an overtube, which is known to cause significant patient discomfort. It is an object of the present invention to enable the capturing, suturing and securing of multiple tissue portions into multiple plications with one intubation and without the need for an overtube.

Referring to FIGS. 1, 19 and 20, a multi-functional sewing device designated generally as **100** is shown separate from an endoscope. The sewing device comprises a generally cylindrical capsule **102** made illustratively from a machined biocompatible metal such as stainless steel or from an injected molded engineering grade of plastic or polymer. Capsule **102** has a modular or integral distal tip **104** that is preferably hemispherical in configuration to enhance ease of advancement through luminal channels or cavities of a mammalian body and to minimize trauma and irritation to the contacted tissue surfaces. Distal tip **104** has portions defining a distal chamber (not shown) that is used to receive a needle or suture tag as described below. Proximal to the distal tip is a suction port **106** adapted to receive tissue suctioned into the port with vacuum pressure. Suction port **106** is preferably formed as an oval or circle to eliminate edges that could irritate suctioned tissue. Suction port **106** opens into a vacuum chamber **108** formed in the body of capsule **102** that is adapted to receive suctioned tissue in preparation for suturing.

A locking sleeve **110** (shown in suction port **106**) extends through a channel (not shown) in the proximal end of capsule **102**. A rigid attachment tube **112** integral to capsule **102** extends proximally from a proximal end of capsule **102** and is dimensioned to fit snugly within the working channel of an endoscope. Tube **112** provides leverage for securing capsule **102** to the distal end of an endoscope along with an attachment ramp **114** that uses a wedge (not shown) to frictionally engage and lock to the endoscope. A lumen of tube **112** is contiguous with the capsule channel through which locking sleeve **110** extends. Formed on a top surface of locking sleeve **110** is a flat surface **116** adapted to receive a suture **118**. Surface **116** provides an essentially low friction abrasion-free passage for suture **118** proximal to its insertion



into a needle **126** shown in FIG. 2. Surface **116** extends proximal to but not into a distal end of locking sleeve **110** to maintain concentricity and radial strength of the distal end.

A pusher **120** is provided to advance and retract needle **126**. Pusher **120** is concentric to locking sleeve **110** and is dimensioned to extend through and slide freely within locking sleeve **110** as well as through and out the proximal end of the endoscope working channel to which capsule **102** is attached. Attached to a proximal end of pusher **120** is pusher handle **122** configured to provide a surface to apply hand pressure with the palm of a hand to advance needle **126** and a finger gripping surface on a distal side to retract needle **126**.

Shown in FIGS. 2, 8 and 9 is a needle assembly designated generally as **124** that is comprised of the locking sleeve **110** and a slotted hypodermic needle **126** with a preferred beveled distal tip **128**. Needle **126** can be made from any suitable biocompatible metal such as stainless steel or polymeric compound such as PEEK (polyetheretherketone), commercially available from Victrex. The compound is a linear aromatic semi-crystalline polymer. A needle suture slot **130** is formed preferably in a central portion of needle **126** to receive in locking engagement suture **118**. Any number of methods can be used to secure suture **118** to needle **126** including crimping, staking, thermo bonding or melting (for needles made from polymeric materials), and knotting. FIGS. 3-8 show a suture locking plug **144** securing suture **118** to needle **126**.

Shown in FIGS. 3-7 is needle **126** releasably locked to pusher **120** through the interaction of mating surfaces formed on the two components. Needle **126** has an inwardly directed annular ring **132** projecting from an inner wall of needle **126**. Pusher **120** has an annular channel **134** dimensioned to conform to the shape of annular ring **132**. Pusher **120** has a cross-sectional diameter that is dimensioned to fit within the inner diameter of needle **126**. A distal tip of pusher **120** is preferably hemispherical in configuration to facilitate registration of pusher **120** in the proximal end of needle **126**. Forward advancement of pusher **120** causes annular channel **134** to engage annular ring **132**. Subsequent forward advancement of locking sleeve **110** secures the engagement of channel **134** to ring **132**. In an alternative embodiment, the proximal portion of ring **132** is removed (not shown) so that the proximal end of needle **126** has

a reduced neck configuration. This configuration eases the release of pusher 120 when retracted out of distal tip 104 subsequent to the retraction of locking sleeve 110.

Slots 127 formed in the annular wall of needle 120 extend from the proximal end toward the distal end, a fraction of the longitudinal length of needle 126. The slots are preferably diametrically opposed 180° and allow for the proximal end of needle 126 to flex radially outwardly. One or more slots can be used; two are preferred. The relative flexibility of the proximal end of needle 126 allows the portion of pusher 120 distal to channel 134 to traverse ring 132 during distal advancement. A sleeve channel 136 formed in the distal end of capsule 102, and concentric with the channel receiving needle 126, is dimensioned to receive in sliding engagement, locking sleeve 110. A distal end 138 of sleeve channel 136 is preferably beveled to the same degree as the distal end 139 of locking sleeve 110. Distal end 138 acts as a stop to prevent needle 126 from being advanced into the inner surface of distal tip 104. A shoulder 140 is formed on the inner surface of locking sleeve 110 for contacting a proximal edge 123 of needle 126 to maintain the concentricity of needle 126 when being urged distally in capsule 102.

Provided in distal tip 102 are detent springs 142, the distal edges of which contact the proximal edge 121 of needle 120. Springs 142 are preferably substantially parallel and oriented perpendicular to the capsule longitudinal axis. The ends of the springs 142 are secured to the inner wall of distal tip 102 by either sitting in annular depressions formed on the inner wall or by mechanical fasteners. Springs 142 are adapted to provide a mechanical stop that prevents needle 126 from being retracted out of distal tip 104 when pusher 120 is retracted. To perform this retention function, any spring can be used that can apply a radial force to needle. Among the possible variants are flat, round and helical springs. The importance of this function is explained below.

To operate this embodiment of the invention, sewing device 100 is back-loaded into the working channel of an endoscope 90 and secured to its distal end as shown in FIGS. 12, 18N and 18O. A suture 118 is secured to needle 124 after being threaded through the working channel of the endoscope and over flat surface 116 of locking sleeve 110. The endoscope/sewing device assembly is advanced through a body lumen to a selected site, preferably within the stomach below the lower esophageal or cardiac sphincter. Once in place, vacuum pressure is commenced in vacuum

chamber 108 from a source external to the endoscope to suction tissue from the body lumen into suction port 106. Needle 126 with attached suture 118 is advanced distally through the tissue and into distal tip 104 of capsule 102. Distal advancement of needle 126 is accomplished by providing a distally directed force to pusher handle 122 that causes distal translation of pusher 120 and needle 126. Preferably, a locking sleeve handle (not shown), attached to the proximal end of locking sleeve 110 and located distal to pusher handle 122, projects proximally from the proximal end of the endoscope, and is advanced simultaneously with pusher handle 122 to ensure a positive lock between needle 126 and pusher 120. Locking sleeve 110 can be maintained in a distally extended position by maintaining manual pressure on the locking sleeve handle or via springs as described in PCT Application No. PCT/US01/07349.

Distal advancement of the pusher/locking sleeve/needle assembly is continued until distal end 139 of locking sleeve 110 contacts distal end 138 of locking channel 136. The distal travel of needle 126 into distal tip 104 results in the proximal end of needle 126 advancing distally past a distal edge 143 of springs 142 as illustrated in FIG. 6. With suture 118 advanced completely through the captured tissue, locking sleeve 110 is proximally retracted to allow for the disengagement of pusher 120 from needle 126 (FIG. 4). Preferably, locking sleeve 110 is retracted until distal end 139 is proximal to vacuum chamber 108.

Proximal retraction of pusher 120 while still engaged to needle 126 causes proximal edge 121 to register with distal edge 143 of spring 142 thereby restraining needle 126 in distal tip 104. Further retraction of pusher 120 coupled with the restraining force provided by spring 142 causes the proximal end of needle 126 to flex radially outwardly thereby disengaging the mating surfaces of ring 132 and channel 134. Needle 126 is cradled in distal tip 104 by the cylindrical opening formed in distal tip 104. To allow for the release of the captured tissue, pusher 120 is retracted proximal to vacuum chamber 108. Following retraction of locking sleeve 110 and pusher 120, the vacuum pressure is terminated which releases the captured tissue.

To prepare sewing device 100 to capture and suture another fold of tissue, pusher 120 is re-advanced through vacuum chamber 108, through springs 142 which expand radially outwardly and into the proximal end of needle 126. Locking sleeve 110 is advanced either simultaneously or slightly behind pusher 120 to lock the

engagement of ring 132 and channel 134. With locking sleeve 110 maintained over pusher 120 and needle 126, pusher handle 122 and handle for locking sleeve 110 are proximally retracted as a unit to retract needle 126 out of distal tip 104. Needle assembly 124 is retracted until substantially proximal to vacuum chamber 108. The cycle is then repeated for a new portion of stomach wall tissue using the same needle and the same suture without the need for multiple intubations. Once the desired number of tissue mounds has been sutured, needle 126 is retracted out the proximal end of locking sleeve 110 to allow removal of needle 126 from the suture. The suture is then threaded into a suture securing device as described below. It is to be noted that the use of the same suture to secure multiple tissue folds allows for the determination of the distance between adjacent tissue folds. Suture 118 is typically provided on a reel having graduations. By monitoring the length of suture being advanced off the reel from one tissue fold to the next, the operator can approximate the distance of the tissue folds.

In an alternative embodiment, a suture tag 150 is used in conjunction with needle 126 to effectuate the suturing of multiple tissue mounds with one intubation. Depicted in FIG. 17, tag 150 is a generally cylindrical in overall shape with a through bore formed preferably along a central longitudinal axis. Formed in a sidewall of tag 150 are notches 152 that are preferably diametrically opposed to engage springs 142. Tags 150 are dimensioned to fit within a channel 129 formed in a needle 126' that is a modified version of needle 126 as shown in FIGS. 15A, 15B and 16. The dimensions of tag 152 are adjusted so that a sidewall of tag 150 frictionally engages an inner wall of needle 126' when locking sleeve 110 is advanced distally over needle 120. The frictional engagement is sufficient to allow for the transfer of tag 150 through capsule 102 with an attached suture 118 but weak enough to be overcome by the radial engagement of springs 142 with detents 152 when locking sleeve 110 is retracted. Needle 126' has a slot 127' that preferably extends the entire length of needle 126' to allow for the needle sidewall to expand radially outwardly to release tag 150. The features of needle 126' that allow engagement with pusher 120 are not shown for purposes of clarity but are the same as those for needle 126. In this embodiment, however, locking sleeve 110 is retracted only from the distal end of needle 126' to allow for the release of tag 152 but not the release of needle 126' from pusher 120.

Operation of this embodiment is graphically illustrated in FIGS. 18A-18I. To begin operation this embodiment, suture 118 is secured to tag 150 via any number of conventional means as described above for the affixation of suture 118 to needle 126. The combination of tag 150 and suture 18 is then mounted in needle 126'. The needle/tag/suture assembly is advanced through locking sleeve 110 via pusher 120 in the same manner as described for needle 126 and as shown in FIG. 18B. Following the suction of a tissue fold into vacuum chamber 108, shown in FIG. 18A, the assembly is forced through tissue mound 95 and into distal tip 104 (FIG. 18C). Springs 142 engage detents 152 upon delivery of tag 152 into distal tip 104. Locking sleeve 110 is partially retracted from the distal end of needle 126' to allow for the release of tag 150. Needle 126' is retracted by proximally retracting pusher 120 in the manner described for needle 126 and as shown in FIG. 18D. The engaging surfaces of detents 152 and springs 142 overcome the frictional engagement of tag 150 to needle 126' and cause the sidewall of needle 126' to flex radially outwardly to release tag 150 which is retained in distal tip 104.

Upon retraction of needle 126' substantially proximal to vacuum chamber 108, suction is terminated to allow for the release of tissue mound 95 with suture 118 secured therein as shown in FIG. 18E. Needle 126' is then distally advanced into distal tip 104 to re-engage tag 150 as shown in FIG. 18F. Sliding sleeve 110 is advanced to an extreme distal position to allow for the capture of tag 150 within needle 126'. The combination of locking sleeve 110, needle 126', tag 150 and pusher 120 are retracted, preferably in unison by simultaneously retracting the pusher handle 122 and the locking sleeve handle to preferably retract the combination proximal to vacuum chamber 108 as shown in FIG. 18G. The process is then repeated with second tissue mound 95' as shown in FIGS. 18H and 18I. An alternate embodiment is shown in FIGS. 10A-10D in which the tag retaining features are eliminated in distal tip 104 and tags 150 are used as anchors, one per tissue mound. In this alternate embodiment, needle assembly is completely removed from the device to allow for additional tags 150 to be secured to the same suture. Once a desired number of tissue mounds have been sutured, the next step is to secure the suture and cinch the mounds together into a plication.

Referring to FIGS. 21, 23 and 24, the distal end of a suture clip delivery and locking catheter is shown generally as 200. Catheter distal end 200 is comprised

primarily of a collet cage 202 to which the other components of distal end 200 are attached. Collet cage 202 is essentially a cylinder with two or more collet fingers 208 extending distally from a distal end of collet cage 202. When viewed from a distal end of collet cage 202, collet fingers 208 preferably form a segmented 360° ring. Extending radially inwardly from a distal end of each collet finger 208 is a collet finger flange 210 that functions as a stop to arrest distal advancement of a suture clip assembly loaded into collet cage 202. The combination of the distal end of collet cage 202, collet fingers 208 and distal flanges 210 define a cage within which the components of a suture clip are releasably encapsulated for delivery to a sutured tissue site. The cage further functions to align the suture clip components for assembly.

In a preferred embodiment, collet finger flanges 210 have radiused outer distal edges 212 to minimize trauma to a patient and radiused inner distal edges 214 to ease loading of suture clip components. In one embodiment (not shown), outer distal edges 212 extend radially outwardly beyond outer walls of collet finger 208 to function as a stop for an outer sliding sleeve 220 described below. Inner proximal faces of collet finger flanges 210 are oriented to a longitudinal axis of the collet fingers so that a plane occupied by flange proximal surfaces 216 forms an angle from about 90° to about 135° and preferably either 135° or 90° with 90° being the most preferred to maximize the stopping function.

Finger slots 218 are formed between and defined by collet fingers 208 and function as egress ports for sutures threaded through the components of a suture clip loaded into collet cage 202. Preferably, collet fingers 208 are biased in an open position so that radial force need only be applied to move the fingers from an open, suture clip loading/releasing position to a closed, suture clip confining position. Alternatively, finger collets 208 can be biased in a closed position as described in PCT Application No. PCT/US01/07349, the contents of which are incorporated herein by reference.

Situated within a hollow chamber defined by the inner walls of collet cage 202 is clip pusher 230 that freely slides within collet cage 202. Pusher 230 is adapted to be proximally advanced into registry with suture clip components to urge the components into engagement with suture 118. Pusher 230 can be a solid rod or a hollow cylinder such as a hypotube.

Situated in coaxial relationship with and freely sliding about collet cage 202 is outer sliding sleeve 220 that performs at least two functions; providing a radially inwardly directed force against collet fingers 208 to maintain the fingers in a closed position during suture clip delivery to a tissue site to minimize potential trauma that could be caused by open collet fingers and providing a means to sever the tail ends of a suture that has been secured with a suture clip. When advanced distally, sliding sleeve 220 encompasses collet fingers 208 and restricts radial movement of the fingers regardless whether the fingers are biased in an open or closed position. In this position, sliding sleeve 220 prevents premature opening of the collet.

When proximally retracted, sliding sleeve 220 severs directly or cooperates with other components to sever suture material proximal to a cinched suture clip. In one embodiment shown in FIGS. 21-24, a suture slot 222 is formed in the sidewall of sliding sleeve 220 preferably in the area occupied by a proximal end of collet cage 202 when sliding sleeve 230 is in its distal most position. As shown in FIGS. 23-25, a collet cage cutting edge 203 is formed in a proximal end of sliding sleeve 220 at or near the distal end of collet cage 202 and extends radially outwardly toward sliding sleeve 220. As shown, a distal end 223 of suture slot 222 engages suture 118 and carries it toward a distal end of the body of collet cage 202. When the distal end 223 of suture slot 222 travels past cutting edge 203, suture 118 is pinched between the surfaces of suture slot 223 and cutting edge 203 that causes the suture to be severed as shown in FIG. 25.

At least one suture slot 223 is formed toward the distal end of sliding sleeve 30 to provide egress for excess suture material that typically extends beyond the orifice through which the catheter is inserted. It is preferred that finger slots 218 and suture slots 223 are at least partially aligned to allow a path for excess suture material to exit the suture clip delivery device. To accomplish alignment, an option alignment slot (not shown) can be formed preferably near a proximal end of sliding sleeve 30. An alignment pin (not shown) is optionally affixed to collet cage 202 and dimensioned to freely slide within the alignment slot. A version of this alignment feature is described and shown in PCT Application No. PCT/US01/07349.

The suture clips used in delivery device 200 are in the preferred form of a ring 260 and a plug 262. As shown in FIGS. 23-25, ring 260 is dimensioned to fit within collet cage 202 such that the concentricity of ring 260 is maintained with respect to the

longitudinal axis of collet cage 202. Plug 262 is preferably of a headless design as shown and dimensioned to frictionally engage an inner wall of ring 260. Plug 262 is preferably formed with tapered ends to facilitate reception of suture 118, to ease insertion into ring 260 and to prevent abrasion of suture 118 between the ends of plug 262 and ring 260. Further details of suture clip components that can be used with delivery device 200 are disclosed in PCT Application No. PCT/US01/07349.

As will be appreciated, the cross-sectional diameter of plug 262 is smaller than the cross-sectional diameter of the outer wall of ring 260. Because of this necessary discrepancy in the dimensions of the suture clip components, accommodation is needed in collet cage 202 to ensure the concentricity of plug 262 when advanced distally into ring 260. One approach is to establish a reduced diameter portion in the proximal end of collet cage 202 to receive and maintain plug 262 in alignment with ring 260. In an alternate embodiment, shown in FIGS. 23-25, a generally cylindrical bushing 205 is provided in the proximal end of collet cage 202 to reduce the complexity of the geometry of the inner walls of collet cage 202. Bushing 205 is adapted to allow for the free axial movement of plug 262 within collet cage 202.

The overall configuration of the suture clip delivery device is shown in FIGS. 26 and 27. A control handle 270 is attached to a proximal end of a collet cage tube 271 that may be in the form of a hypotube. A distal end of tube 271 is attached to the proximal end of collet cage 202. Tube 271 has an inner diameter that is adapted to receive clip pusher 230 that slides freely within tube 271. To operate the working features of the delivery device, two control surfaces are provided for advancing and retracting the various sliding components. The first, clip pusher handle 232, is attached to the proximal end of clip pusher 230. The second is sliding sleeve handle 274 which is attached to a proximal end of a sliding sleeve tube 276, the distal end of which comprises sliding sleeve 220. Sliding sleeve tube 276 may be in the form of a hypotube with an inner diameter dimensioned to receive collet cage tube 271 that slides freely within sliding sleeve tube 276. Clip pusher 230, collet cage tube 271 and sliding sleeve tube 276 are all coaxially arranged to allow the system to be dimensioned to slide freely within the working channel of endoscope 90 and the needle assembly channel of capsule 102.

To operate the suture clip delivery device, clip pusher handle 232 and sliding sleeve handle 274 are retracted to allow collet fingers 208 to spring radially outwardly



to receive the suture clip components, plug 262 and ring 260. Next, suture 118 previously placed into a plurality of tissue mounds is threaded through ring 260, collet cage 202 and out suture slot 222. The ends of the suture are maintained out of the delivery device and endoscope 90.

With the suture threaded through the suture clip delivery device, the device is distally advanced through the working channel of endoscope 90, into the proximal end of capsule 102 and into vacuum chamber 108 as shown in FIGS. 18J, 18K and 22. The device is now in a position to begin the suture cinching procedure. Because of inherent flexibility in the device, collet cage 202 may slightly rotate out of axial alignment with the longitudinal axis of capsule 102 toward the sutured tissue mounds via the tension created by suture 118. This is a desired effect as it allows the distal end of collet cage 202 to come into closer proximity to the last tissue mound sutured. This maximizes the potential to provide a tight plication since suture slack can be minimized. In short, the tissue mounds can be cinched closer together the closer collet cage 202 can be situated to the tissue mounds.

The cinching process begins by providing a distally directed force onto clip pusher handle 232. This causes the forward advancement of pusher 230 into registration with the proximal end of plug 262 that, in turn, is urged distally into ring 260 to thereby capture suture 118 via the frictional engagement of plug 262 to ring 260. Once plug 262 has been preferably fully engaged to ring 260, sliding sleeve handle 274 can be proximally retracted to sever the excess suture 118 and to allow collet fingers 208 to flex radially outwardly to allow for the release of the cinched suture clip as shown in FIG. 18L. The plication formed according to the procedure described herein forms a figure 8 suture pattern with an attached suture clip as shown in FIG. 13. FIGS. 11 and 14 show a plication formed with the use of tag 150 as an anchor with twists in the tissue mounds and suture paths shown with directional arrows. The delivery device can then be retracted out of capsule 102 and endoscope 90 to end the procedure or to prepare for another cycle of suturing and suture cinching. At all times during the procedure or multiple cycles of the procedures described herein, endoscope 90 and capsule 102 can be maintained in the patient with a single intubation event. Endoscope is simply maneuvered to the desired tissue locations to perform the gastropasty procedure.

It should be understood that the foregoing description of the invention is intended merely to be illustrative thereof and that other modifications, embodiments and equivalents may be apparent to those who are skilled in the art without departing from its spirit. Having thus described the invention what we desire to claim and secure by letters patent is:

**Claims**

1. A tissue apposition and suturing device for use with an endoscope comprising:  
a tissue suturing capsule having a channel formed therein; and  
a suture clip delivery device adapted for axial displacement within the channel.
2. The device of claim 1 further comprising:  
a needle adapted for axial displacement within the channel.
3. The device of claim 2 further comprising:  
a pusher having surfaces adapted to engage with surfaces of the needle.
4. The device of claim 3 further comprising:  
a control handle attached to a proximal end of the pusher.
5. The device of claim 4 wherein the capsule further comprises a distal tip having  
a cavity formed therein.
6. The device of claim 5 further comprising:  
a pair of springs mounted in the cavity.
7. The device of claim 6 further comprising:  
a locking sleeve having a through bore for receiving the needle.
8. The device of claim 7 further comprising:  
a tag adapted to be received within the needle.
9. The device of claim 1 wherein the suture clip delivery device further comprises

a collet having a body and a plurality of collet fingers extending from a distal end of the body;

a hypotube connecting the control handle to the collet;

an outer sleeve situated coaxially about the collet such that the sleeve freely slides along a longitudinal axis; and

a pusher situated coaxially within the collet that freely slides along a longitudinal axis of the delivery catheter.

10. The device of claim 9 wherein the plurality of collet fingers further comprise flanges extended radially inwardly from a distal end of each of the plurality of collet fingers.

11. The device of claim 10 wherein at least one of the plurality of collet fingers has a ramp formed on an inside wall that tapers radially inwardly from a proximal to a distal end such that the combination of the collet fingers, ramp and flanges define a suture clip cage.

12. The device of claim 10 wherein the flanges are radiused on outer and inner distal edges.

13. The device of claim 9 wherein each of the plurality of collet fingers has sidewalls that define finger slots.

14. The device of claim 13 wherein the outer sleeve has portions defining at least one suture slot situated proximal to a distal end of the sleeve.

15. The device of claim 14 wherein the sleeve has further portions defining an alignment slot situated proximal to the suture slot.

16. The device of claim 15 wherein the collet has an alignment pin formed on an outer collet wall adapted to engage and slide within the alignment slot such that at least one of the finger slots radially aligns with the suture slot.
17. The device of claim 16 wherein the at least one finger slot longitudinally aligns with at least a portion of the suture slot.
18. The device of claim 10 wherein a proximal face of the flanges forms an inclusive angle with a longitudinal axis of an adjoining collet finger of from about 90° to about 135°.
20. The device of claim 1 further comprising:  
a collet having a body and a plurality of collet fingers extending from a distal end of the body;  
an outer sleeve situated coaxially about the collet such that the sleeve freely slides along a longitudinal axis;  
a first pusher situated coaxially within the collet that freely slides along a longitudinal axis; and  
a second pusher situated coaxially about the first pusher and coaxially within the collet that freely slides along a longitudinal axis.
21. The device of claim 20 wherein the plurality of collet fingers further comprise flanges extended radially inwardly from a distal end of each of the plurality of collet fingers.
22. The device of claim 21 wherein at least one of the plurality of collet fingers has a ramp formed on an inside wall that tapers radially inwardly from a proximal to a

distal end such that the combination of the collet fingers, ramp and flanges define a suture clip cage.

23. The device of claim 21 wherein the flanges are radiused on outer and inner distal edges.

24. The device of claim 20 wherein each of the plurality of collet fingers has sidewalls that define finger slots.

25. The device of claim 24 wherein the outer sleeve has portions defining at least one suture slot situated proximal to a distal end of the sleeve.

26. The device of claim 25 wherein the sleeve has further portions defining an alignment slot situated proximal to the suture slot.

27. The device of claim 26 wherein the collet has an alignment pin formed on an outer collet wall adapted to engage and slide within the alignment slot such that at least one of the finger slots radially aligns with the suture slot.

28. The device of claim 27 wherein the at least one finger slot longitudinally aligns with at least a portion of the suture slot.

29. The catheter of claim 21 wherein a proximal face of the flanges forms an inclusive angle with a longitudinal axis of an adjoining collet finger of from about 90° to about 135°

30. The catheter of claim 22 wherein a distal end of the second pusher is tapered to matingly engage the ramp when the second pusher is distally advanced.

22. A method of capturing, suturing and securing a suture to a tissue fold comprising:

providing a capsule having a channel formed therein;

suctioning a tissue fold into the capsule;

providing a suture attached to a needle;

advancing the needle and suture into and through the tissue fold;

retracting the needle;

providing a suture clip delivery device adapted to slide within the capsule channel;

advancing the delivery device into the capsule via the channel;

providing a suture clip in the delivery device;

capturing the suture with the suture clip; and

releasing the suture clip from the delivery device.

**AMENDED CLAIMS**

[received by the International Bureau on 12 November 2001 (12.11.01);  
original claims 1-22 replaced by new claims 1-45 (6 pages)]

1. A combination tissue apposition device and suture clip delivery device for use with an endoscope comprising:
  - a tissue apposition device having portions defining a channel; and
  - a suture clip delivery device that freely slides within the channel.
2. The device of claim 1 further comprising:
  - a needle adapted for axial displacement within the channel.
3. The device of claim 2 further comprising:
  - a pusher having surfaces adapted to releasably lock with surfaces of the needle.
4. The device of claim 3 further comprising:
  - a control handle attached to a proximal end of the pusher.
5. The device of claim 4 wherein the tissue apposition device comprises a capsule.
6. The device of claim 5 wherein the capsule defines a suction port and a vacuum chamber adjacent to and in communication with the suction port.
7. The device of claim 6 wherein the vacuum chamber is in communication with the channel.
8. The device of claim 7 wherein the capsule further comprises a distal tip having a cavity formed therein.
9. The device of claim 8 wherein the capsule further comprises at least two springs mounted in a substantially parallel arrangement in the cavity.
10. The device of claim 9 wherein the apposition device further comprises a locking sleeve having a through bore for receiving the needle and pusher wherein



the locking sleeve is coaxially arranged about, and freely slides axially about the needle and pusher.

11. The device of claim 10 wherein the needle has an annular ring extending radially inwardly.
12. The device of claim 11 wherein the needle comprises at least one slot formed along a partial length of the needle.
13. The device of claim 12 wherein the pusher has an annular channel configured to matingly engage the needle annular ring.
14. The device of claim 13 wherein the locking sleeve is dimensioned to radially compress the needle against the pusher whereby the annular ring engages the annular channel to prevent relative axial movement of the needle and pusher.
15. The device of claim 14 wherein the at least two springs are spaced a predetermined distance to allow the needle to advance distally past the at least two springs and whereby the springs flex radially outwardly when the needle is advancing through the spaced springs and flex radially inwardly to a resting position when a proximal end of the needle is distal to distal faces of the springs.
16. The device of claim 15 further comprising:  
a tag adapted to be received within the needle.
17. The device of claim 16 wherein the needle has a surface for receiving a suture.
18. The device of claim 17 wherein the needle has a cavity for receiving a plug dimensioned to frictionally engage the cavity wherein the suture is frictionally engaged between the cavity walls and the plug.
19. The device of claim 1 wherein the suture clip delivery device further comprises

a collet having a body and a plurality of collet fingers extending from a distal end of the body;

a hypotube connecting the control handle to the collet;

an outer sleeve situated coaxially about the collet such that the sleeve freely slides along a longitudinal axis; and

a pusher situated coaxially within the collet that freely slides along a longitudinal axis of the delivery catheter.

20. The device of claim 19 wherein the plurality of collet fingers further comprise flanges extended radially inwardly from a distal end of each of the plurality of collet fingers.

21. The device of claim 20 wherein at least one of the plurality of collet fingers has a ramp formed on an inside wall that tapers radially inwardly from a proximal to a distal end such that the combination of the collet fingers, ramp and flanges define a suture clip cage.

22. The device of claim 21 wherein the flanges are radiused on outer and inner distal edges.

23. The device of claim 22 wherein each of the plurality of collet fingers has sidewalls that define finger slots.

24. The device of claim 23 wherein the outer sleeve has portions defining at least one suture slot situated proximal to a distal end of the sleeve.

25. The device of claim 24 wherein the sleeve has further portions defining an alignment slot situated proximal to the suture slot.

26. The device of claim 25 wherein the collet has an alignment pin formed on an outer collet wall adapted to engage and slide within the alignment slot such that at least one of the finger slots radially aligns with the suture slot.

27. The device of claim 26 wherein the at least one finger slot longitudinally aligns with at least a portion of the suture slot.

28. The device of claim 27 wherein a proximal face of the flanges forms an inclusive angle with a longitudinal axis of an adjoined collet finger of from about 90° to about 135°.

29. The device of claim 1 further comprising:

a collet having a body and a plurality of collet fingers extending from a distal end of the body;

an outer sleeve situated coaxially about the collet such that the sleeve freely slides along a longitudinal axis;

a first pusher situated coaxially within the collet that freely slides along a longitudinal axis; and

a second pusher situated coaxially about the first pusher and coaxially within the collet that freely slides along a longitudinal axis.

30. The device of claim 29 wherein the plurality of collet fingers further comprise flanges extended radially inwardly from a distal end of each of the plurality of collet fingers.

31. The device of claim 30 wherein at least one of the plurality of collet fingers has a ramp formed on an inside wall that tapers radially inwardly from a proximal to a distal end such that the combination of the collet fingers, ramp and flanges define a suture clip cage.

32. The device of claim 31 wherein the flanges are radiused on outer and inner distal edges.

33. The device of claim 32 wherein each of the plurality of collet fingers has sidewalls that define finger slots.

34. The device of claim 33 wherein the outer sleeve has portions defining at least one suture slot situated proximal to a distal end of the sleeve.

35. The device of claim 34 wherein the sleeve has further portions defining an alignment slot situated proximal to the suture slot.
36. The device of claim 35 wherein the collet has an alignment pin formed on an outer collet wall adapted to engage and slide within the alignment slot such that at least one of the finger slots radially aligns with the suture slot.
37. The device of claim 36 wherein the at least one finger slot longitudinally aligns with at least a portion of the suture slot.
38. The catheter of claim 37 wherein a proximal face of the flanges forms an inclusive angle with a longitudinal axis of an adjoined collet finger of from about 90° to about 135°
39. The catheter of claim 38 wherein a distal end of the second pusher is tapered to matingly engage the ramp when the second pusher is distally advanced.
40. A method of collecting, sewing and securing tissue folds with one intubation comprising:  
collecting body tissue;  
sewing body tissue into folds with at least one suture;  
securing the at least one suture against the body tissue to secure the folds.
41. A method of sewing and securing tissue comprising:  
advancing a tissue apposition device into a body cavity having cavity walls;  
collecting tissue from the cavity walls and configuring the tissue into a fold;  
sewing the folds with at least one suture;  
inserting a suture clip delivery device into the apposition device;  
securing the at least one suture to the fold with the suture clip delivery device.
42. The method of claim 41 further comprising:  
providing a tissue apposition device with a capsule having a vacuum chamber and channel formed therein;  
suctioning a tissue fold into the capsule;

providing a suture and a needle wherein the suture is attached to the needle;  
advancing the needle and suture through the channel and into and through  
the tissue fold;

depositing the needle in a distal cavity formed in a distal tip of the capsule;

removing the suction to release the sutured tissue fold;

retracting the needle;

providing a suture clip delivery device adapted to slide within the capsule  
channel;

advancing the delivery device into the capsule via the channel;

providing a suture clip in the delivery device;

capturing the suture with the suture clip; and

releasing the suture clip from the delivery device.

43. The method of claim 42 further comprising:

providing a tag within the needle wherein the tag is attached to the suture;

advancing the tag and needle through the tissue fold;

depositing the tag in the distal tip cavity; and;

retracting the needle.

44. The method of claim 43 further comprising:

re-advancing the needle into the distal tip cavity;

retracting the tag and needle proximal to the vacuum chamber;

suctioning a second tissue fold into the capsule;

advancing the tag and needle through the tissue fold into the distal tip cavity;

re-depositing the tag in the distal tip cavity; and,

retracting the needle.

45. The method of claim 41 further comprising:

suctioning a second section of tissue into the capsule to form a second tissue  
fold;

advancing the needle through the second tissue fold;

depositing the needle in the distal end cavity;

removing the suction to release the second tissue fold from the capsule; and,

retracting the needle.

1/29




FIG. 1

2/29




FIG. 2

3/29




FIG. 3



4/29




FIG. 4

5/29




FIG. 5

6/29




FIG. 6

7/29




FIG. 7

8/29




FIG. 8

9/29




FIG. 9

10/29




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D

11/29




FIG. 11



12/29




FIG. 12

13/29




FIG. 13




FIG. 14

14/29




FIG. 15A




FIG. 15B




FIG. 16

15/29




FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E  
SUBSTITUTE SHEET (RULE 26)




FIG. 18F




FIG. 18G




FIG. 18H




FIG. 18I









FIG. 18J  
SUBSTITUTE SHEET (RULE 26)

18/29



19/29




FIG. 19






FIG. 20




FIG. 21

22/29




FIG. 22




FIG. 23

24/29





FIG. 24



26/29





FIG. 26








FIG. 28A  
(PRIOR ART)




FIG. 29  
(PRIOR ART)




FIG. 30  
(PRIOR ART)

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US01/16025**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(7) : A61B 17/10

US CL : 606/139

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 606/139, 142, 144, 145, 148, 232, 233

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST BRS

search terms: suture, collet, fingers, clip, capsule

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,910,105 A (SWAIN et al.) 08 June 1999, figs. 1-3.	1-5
A	US 5,931,844 A (THOMPSON et al.) 03 August 1999, see entire document.	1-22
A, P	US 6,086,608 A (EK et al.) 11 July 2000, see entire document.	1-22

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier document published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"G" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

30 JULY 2001

Date of mailing of the international search report

10 SEP 2001

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

JULIAN W. WOO

Telephone No. (703) 308-0421

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**